



Waterlogic 4 Firewall™

The Waterlogic 4 dispenser uses Firewall™ UV light to wipe out impurities. It's in an innovative piece of technology which has been designed by us to produce the purest water. It purifies drinking water, cleansing the water to 99.9999% bacteria free, and acts as a barrier, maintaining hygiene of the dispenser. Our unique design also results in high capacity to provide hot, cold, ambient, or sparkling water, whenever you want it.

The Waterlogic Firewall guarantees a microbiologically pure, fresh and clean glass of water for every user throughout the day.

Three Steps to Greatness

Your Waterlogic dispenser has 3 core technologies which mean that what you get out of your machine is much better than what goes in:



1. Filtration: Our filtration technology is really good at taking the bad stuff out and leaving the good stuff in. This stage removes chlorine and other waterborne tastes and odours.*



2. Firewall™: Next the Firewall UV purification will wipe out impurities, cleansing pathogens from the water by up to 99.999%. As an added layer of protection, the UV light keeps the dispensing nozzle from becoming contaminated.



3. BioCote®: We've got the inside covered and the outside too. As another layer of defence, BioCote keeps the dispensing area free from bacteria.





* Dependant on filter type used and water conditions

Photo: Waterlogic 4 Firewall counter top version with optional base unit for conversion to freestanding.



Performance Worthy of an Encore

Our Firewall™ technology is unique for 3 reasons:



The design allows for higher UV exposure which reduces bacteria, viruses and parasites that may be in the water the water, purifying up to 99.9999% of any pathogens 100% of the time.

2. Goodbye bacterial contamination

Point of dispense purification keeps the dispense nozzle free from external contamination as well as purifying the water as it fills your cup, making the freshest water possible.

3. Certified, twice

The Firewall™ technology has been tested and certified by the WQA to NSF/ANSI-55 Class A UV and NSF P231 protocol (coming soon), which is unique – no one else has these together. This means that Firewall delivers the cleanest, clearest water possible.





The Boring Bits

Water Options	Technical Features	
	Type available	Countertop Freestanding
	Countertop dimensions	418mm (W) x 439mm (H) x 470mm (D) 16.5" (W) x 17.3" (H) x 18.5" (D)
	Freestanding dimensions	418mm (W) x 1242mm (H) x 470mm (D) 16.5" (W) x 48.9" (H) x 18.5" (D)
	Dispense area height	240mm (9.5")
	Weight	Countertop: 24-35kg Freestanding: 42-53kg
	Standard filtration supplied	1 x Carbon Block (CBC) and 1 x Granular Activated Carbon (GAC)
Symbols Ambient water	Additional features	Filter timer Firewall UV sensor Drip tray overflow Thermal overload Sleep mode Leak detection
Cold water	Capacity	Hot tank: 1.2 litres (0.317 US gal.) Cold tank: 4.5 litres (1.19 US gal.)
Sparkling water	Compressor	220/240V 50Hz or 110/120v 60Hz
Hot water Extra Hot water	Water temperatures	Cold: 6°-9°C / 42.8-48.2°F Hot: 87°C / 188.6°F Extra hot: 93°C / 199.4°F

Tested and Certified













Waterlogic International Limited and WLI Trading Limited reserves the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLT Trading Ltd is licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.



Call us: 01823 698953

Email us: info@mastervendsw.co.uk Visit us: www.mastervendsw.co.uk